

Get the film-like imaging of DLP® technology with new BrilliantColor™ color reproduction in a Large Venue High Definition projector.

EIKI-HDT30

Key Features

- ◆ Full HD 1080p resolution. 8000 Lumens brightness. 7,500:1 contrast ratio.
- ◆ Single Chip DLP® imaging technology delivers a "seamless" image.
- ◆ Upscales 720p. Supports other widescreen and standard aspect ratios.
- ◆ Included 6-segment dual color wheel set can be installed, for Rich Color.
- ◆ 2 fixed inputs include a full suite of standard professional connections.
- ◆ 2 module bays permit customization. Built-in LAN Control Port.
- ◆ Optional modules include Dual (HD/SD) SDI and HD Wireless Receiver.
- ◆ Both horizontal & vertical power lens shift. Built-in Mechanical Shutter.
- ◆ Power Zoom and Focus. Optional Wideangle and Telephoto lenses.
- ◆ Centered lens and one-way airflow simplify installation. Quick lens installation
- ◆ Dual Lamp System provides redundancy and permits 4 brightness levels.
- ◆ Illuminated control panel & wireless/wired remote. RS-232 & Network control.
- ◆ Power Management, Keylock Security, and Custom Warmup Screen options.
- ◆ 3 Year* Projector Warranty!

Outstanding Features

1. 1080p at 8000 Lumens, 7500:1 Contrast, with DLP® imaging.
2. User-changeable color wheels to optimize brightness or color.
3. Lamp Interval Timer permits alternate 1-lamp-ON in 24/7 use.
4. Low Maintenance: up-to 35,000 hour cartridge air filter.
5. Extended Use: Peltier device cooled DMD®, sealed optical engine.
6. Picture-in-Picture. Picture-by-Picture. Edge Blending.
7. Power zoom, focus, lens shift. Range of lenses and modules.



**8,000 Lumens
Full HD-1080p DLP® Theater Projector
with enhanced color reproduction**



EIKI
Projectors... and more!

SPECIFICATIONS:


Brightness	up to 8,000 ANSI Lumens (**w/lens AH-43005S) ("Dynamic" image mode & DynamicBlack™ Off)
Illumination Uniformity	90%
Color Reproduction	10 bit/1.07 Billion Colors
Contrast Ratio	up to 7,500:1 (w/DynamicBlack™ high)
Projection Lamp	330 Watt VIDI™ UHP x 2
Estimated Lamp Life	up to 3000 Hours of Use
Imaging System	0.95" DarkChip™ 1-chip DLP® x 1
Native Resolution	192x1080 (16:9 aspect ratio)
Color System	High Brightness 4-segment color wheels x 2 (installed)
Lens	Not Included (choose from a selection of optional lenses)
Image Diagonal	50-600 in
Image Width	3.64-43.6 ft (1.11-13.20 m)
Throw Distance	See specifications of selected lens
Front Elevation / Maximum Pitch	up to 5° up/360°
Vertical Anti Keystone	Power Lens Shift (Top:Bottom) 6.65:1~1:6.65
Horizontal Anti Keystone	Power Lens Shift (L:R:R:L) 10.7:1~1:10.7
Vertical Keystone Correction	Digital: up-to 30° up or down
Horizontal Keystone Correction	Digital: up-to 30° left or right
Scanning Frequency	Auto: H Sync. 15-120 kHz; V Sync. 48-120 Hz
Dot Clock	up to 230 MHz
Image Orientation	Normal, Reversed, Inverted
Local Control / Power Management	Full Function / Auto Shut-Off
Remote Projector Control	Wireless / Wired x 1
Wired Remote Port	MiniStereo x 1
Projector Service Port	USB-B x 1
RS-232 (Serial) Port / In & Out	Dsub 9-pin x 1
Wired LAN Control Port	RJ45 x 1
Computer: Compatibility	UXGA (analog only), WUXGA-WXGA, SXGA+-VGA & MAC (analog or digital)
Computer: Formats	1920x1200 through 640x480
Computer: Image Sizing	Normal, or Smart Compressed or Expanded
Video: Color Systems	NTSC / PAL / SECAM / NTSC 4.43 / PAL-M&N
Video: Aspect Ratios Supported	16:9, 4:3 and other
Video: Image Resizing	Video Scaling Technology
Video: Resolutions Supported	
SDTV (Composite, S-Video, Component)	480i/p, 575i/p
HDTV	720p 1080i/p, 1080 psf 30/25/24
Signal Inputs: fixed	
1. a. Computer: Analog RGB	Dsub15 x 1
b. Computer: Digital RGB	DVI-D x 1
or Video: Digital Video w/HDCP	
c. Video: Digital Video (w/HDCP)	HDMI x 1
2. a. Computer: Analog RGBHV	BNC x 5
or Video: Composite / Component: Video / Y-Pb/Cb-Pr/Cr	
b. Video: S-Video	S-Video x 1
Signal Inputs: modules	
3. Empty module bay (unpopulated)	
4. Empty module bay (unpopulated)	
Signal Outputs:	
Data / Video Monitor: Analog RGB / Composite / Component	Dsub15 x 1
Operating Noise	as low as 35 dBA
Cabinet Size (HxWxD)	9.6 x 15.7 x 20.6 in (242.5 x 400 x 524.2 mm)
Weight	43.2 lb (19.6 kg)
Packaged Size (HxWxD)	17.3 x 20.8 x 25.6 in (439 x 528 x 651 mm)
Packaged Weight	54.2 lb (24.6 kg)
Power Requirements	100-240V AC, 50/60Hz
Power Consumption	up to 963W Standard Mode
Heat	up to 3286 BTU/hr (772Kcal/hr)
Power Cord	Type 3, Detachable
Electrical Safety Compliance	UL / cUL
Electromagnetic Compatibility	FCC Part 15 Class A
Security	Kensington® Security Slot, Handles (use as Security Bar)
Operating Temperature	41-104°F (5-40°C)
User Maintenance	Replace Air Filter, Replace Lamps
Warranty: (to the original end-use customer)	
Projector:	3 Years (Parts & Labor to Correct Defects)
Lamp:	6 months ownership / 500 hours use (whichever occurs first)




EIP-HDT30 – Full HD-1080p DLP® Theater Projector with enhanced color reproduction.



Complete local control, professional inputs, 2 expansion bays.



Top-accessed color wheels & lamps.



Full-function remote control.

INCLUDED ACCESSORIES:

Quick Setup Guide. Owner's Manual on CD-ROM. 6 ft (1.8 M) AC Power Cord. Lens Cover. VGA-type Computer Input Cable (Dsub15). Wireless/wired Remote & 2 x AA batteries. Wired Remote Cable. Real Color Manager Pro Software on CD-ROM x 1. Cable Cover x 1. Cable Cover Support x 1. Cable tie x 3. Rich Color 6-Segment Color Wheels x 2. Lens Aperture Cover.

OPTIONAL ACCESSORIES:

Wideangle, Standard and Telephoto Lenses. Replacement Lamps. Replacement Filter Cartridge. ATA-Style Shipping Case with Wheels and Telescoping Handle. Dual SDI Module (only HD-SDI can be used). DVI (only) Module. DVI-D & Dsub15 Module. 5BNC Module. 5BNC & S-Video Module. Dsub15 Module. Network Module. Ceiling Mount. Ceiling Post and Plate. HD Data Wireless Receiver Module. HD Wireless Transmitter.

EIKI® is a registered trademark of Eiki International, Inc.

Eiki International, Inc.

30251 Esperanza, Rancho Santa Margarita, CA 92688-2130
 Tel: 800-242-3454; Fax: 800-457-3454, E-mail: usa@eiki.com
 In Canada, 310 First St.-Unit 2, P.O. Box 156, Midland, ON L4R 4K8
 Phone: 800-563-3454, Fax: 800-567-4069 E-mail: canada@eiki.com

<http://www.eiki.com>

